



## DULUX INSPIRE INTERIOR

C1510378 LINE (WATERBASED)

### PRODUCT INFORMATION

<b>PRODUCT NAME</b>	Dulux Inspire Interior
<b>Product Code</b>	C1510378
<b>DESCRIPTION</b>	Dulux Inspire Interior is a good quality, durable and washable emulsion with advanced Chroma Brite Technology that keeps your house looking fresh and new for a longer period of time. Dulux Inspire Interior also delivers smooth sheen finish and provides good coverage. In compliance to SIRIM Eco Label and Singapore Green Label.
<b>USAGE</b>	Dulux Inspire Interior is suitable for all normal interior wall and ceiling surfaces.
<b>BENEFITS</b>	Attractive mid-sheen finish. Good coverage
<b>PACK SIZE</b>	1, 5 and 18 litres
<b>COLOR RANGE</b>	See Dulux Inspire Colour Catalogue.

### PERFORMANCE GUIDE

<b>FILM PROPERTIES</b> Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing. Not suitable where frequent heavy condensation is likely, as in kitchens and bathrooms.
<b>THEORETICAL COVERAGE</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 10 - 11 m <sup>2</sup> /L.

### PRODUCT DATA

<b>COMPOSITION</b> (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Copolymer Emulsion. Solvent : Water.
<b>VOLUME SOLIDS</b>	White 34% (nominal), other colours will vary.

### APPLICATION

<b>THINNING</b> Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 10 parts of paint (10%). For normal use thinning is usually not necessary.
Conventional Spray Airless Spray	Add up to 1 part of clean water to 3 parts of paint (30%). Ready for use. Thinning is usually not required.
<b>DRYING TIMES</b> Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 2-3 hours.
<b>CLEANING UP</b>	Clean all equipment with clean water immediately after use.

## PRE-APPLICATION

<b>SURFACE PREPARATION</b>	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These wall should be left to dry further.	
<b>SYSTEM INFORMATION</b> Powdery Surfaces  Alkaline and New Surfaces  Normal, Sound Surfaces	<b>PRIMER (1 COAT)</b>  Dulux Adhesion Promoting Interior Wall Primer (A579-15458)  Dulux Exterior & Interior Wall Sealer (A1290013 0015527)  No Primer Required	<b>FINISH (2 COATS)*</b> Vibrant/ deep shade may require additional coats.  Dulux Inspire Interior

## PRECAUTION

<b>HEALTH, SAFETY AND ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"> <li>• Keep out of the reach of children</li> <li>• Do not breathe vapour/ spray</li> <li>• Use only in well ventilated areas</li> <li>• Safety data sheet available for professional user on request.</li> <li>• Avoid contact with skin or eyes</li> <li>• If swallowed seek medical advice immediately and show this container or label.</li> <li>• Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used</li> <li>• Do not use empty container for storing food.</li> <li>• Remove as much paints as possible from brushes and rollers before cleaning.</li> <li>• Keep away from food, drinks and animal feed.</li> <li>• Store in a cool and shaded place.</li> <li>• Container must be in a secure, upright position and be tightly closed.</li> <li>• In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>• In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.</li> <li>• Wear eye/hand protection.</li> <li>• Avoid release to environment. Refer to special instructions/Safety data sheet.</li> <li>• Do not empty into water course.</li> <li>• Dispose of used container in compliance with local regulation.</li> <li>• Refer to Dulux Product Safety Data Sheet for further details.</li> <li>• In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187</li> </ul>
---	---

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

### Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: [www.dulux.com.my](http://www.dulux.com.my) Email: [customercare.my@akzonobel.com](mailto:customercare.my@akzonobel.com)