



## DULUX EASYCLEAN

MATT FINISH

WATER BASED

### PRODUCT INFORMATION

<b>PRODUCT NAME</b>	Dulux EasyClean
<b>DESCRIPTION</b>	Dulux EasyClean is a premium interior quality matt finish paint that provides good stain resistance which allows you to clean common household stains off your wall easily. Now with Anti-bacterial functionality, it aids to inhibit the growth of bacteria* on the walls. Formulated with Dulux Colourguard Technology, it locks in colours to keep your wall looking beautiful for longer.
<b>USAGE</b>	Dulux EasyClean is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement and wallboards.
<b>BENEFITS</b>	<p>Good stain resistance with common household stains.</p> <p>Good washability.</p> <p>Anti-bacterial properties that aids to inhibit growth of certain bacterial* on the walls.</p> <p>Colourguard Technology that locks in the colour.</p> <p>Low Odour &amp; Low VOC<sup>^</sup>.</p> <p>Singapore Green Label and SIRIM Eco-label certified<sup>^</sup>.</p> <p><sup>^</sup> Applicable to selection colours only.</p> <p>No added lead &amp; mercury.</p> <p><u>Note:</u></p> <p>* Under test conditions. Dulux EasyClean tested against 6 types of bacteria as per JIS Z 2801:2010 Antibacterial products – Test for antibacterial activity and efficacy to meet the anti-bacterial performance requirements for the following set of bacteria:</p> <ul style="list-style-type: none"> <li>- Pseudomonas aeruginosa (ATCC 9027)</li> <li>- Staphylococcus aureus (ATCC 6538P)</li> <li>- Bacillus subtilis (ATC 6633)</li> <li>- Salmonella typhimurium (ATCC 14028)</li> <li>- MRSA (NCTC 12493)</li> <li>- Escherichia coli (ATCC 8739)</li> </ul>
<b>PACK SIZE</b>	1, 5 and 18 litres
<b>COLOUR RANGE</b>	Refer to Dulux colour catalogue

### PERFORMANCE GUIDE

<b>FILM PROPERTIES</b>	Will tolerate the levels of atmospheric humidity present in normal interior environments and able to withstand any washing or cleaning the wall with mild detergent only after the paint has cured for at least 7 days. Stain resistance effective for common household stains.
<b>THEORETICAL COVERAGE</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 12m <sup>2</sup> /litre.

### PRODUCT DATA

<b>COMPOSITION</b> (nominal)	<p>Pigment : Lightfast non-lead pigments and mineral extenders</p> <p>Binder : Acrylic copolymer</p> <p>Solvent : Water</p>
<b>VOLUME SOLIDS</b>	White 35% (nominal), other colours will vary.



## DULUX EASYCLEAN

MATT FINISH

WATER BASED

### PRODUCT INFORMATION

#### APPLICATION

##### THINNING

Brush or Roller

For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).

Conventional Spray

Add up to 1 part of clean water to 3 parts of paint (30%).

Airless Spray

Ready for use. Thinning is usually not required.

##### SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm<sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°

##### DRYING TIMES

Touch Dry

Single coat at standard thickness:

Recoat

Dependant on temperature and humidity

2-3 hours

##### CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

#### PRE-APPLICATION

##### SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Dulux Sealer/Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 16%. These walls should be left to dry further.

##### SYSTEM INFORMATION

Powdery Surfaces

##### SEALER/PRIMER (1 COAT)

##### FINISH (MINIMUM 2 COATS)

Alkaline and/or New Surfaces

Dulux Weathershield Primer

Normal, Sound Surfaces

Dulux Exterior & Interior Wall Sealer

Dulux Exterior & Interior Wall Sealer

Dulux EasyClean

(Colour enhancer is advisable for vibrant colour)

#### PRECAUTION

##### HEALTH, SAFETY AND ENVIRONMENT INFORMATION

Product Safety Data Sheet available upon request

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties

EC: 210722

Akzo Nobel Paints (Malaysia) Sdn Bhd  
(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: [www.dulux.com.my](http://www.dulux.com.my) Email: [customer care.my@akzonobel.com](mailto:customer care.my@akzonobel.com)

**AkzoNobel**