



DULUX EASYCLEAN PLUS

SHEEN FINISH

WATER BASED

PRODUCT INFORMATION

PRODUCT NAME	Dulux EasyClean Plus
PRODUCT CODE	A990 Line
DESCRIPTION	<p>Dulux EasyClean is a premium interior quality sheen finish paint KidProof+ technology that delays stains from penetrating further into the paint film and can be wiped away easily. With its anti-bacterial property, it also aids to inhibit growth of certain bacteria (*) on walls.</p> <p>Now with new Silver Ion Technology, it comes with an added benefit of anti-virus property that helps to effectively work against certain virus (**).</p> <p>Dulux EasyClean Plus provides protection for your walls not only from stains but also certain bacteria and virus.</p>
USAGE	Dulux EasyClean Plus is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement and wallboards.
BENEFITS	<p>KidProof+ technology - delays stains from penetrating into the paint film and can be wiped away easily. It also comes with anti-bacterial property that aids to inhibit growth of certain bacteria (*) on the walls.</p> <p>Silver Ion Technology - added benefits of anti-virus property that helps to effectively work against certain virus (**).</p> <p>Colourguard technology that locks in the colour.</p> <p>Low Odour & Low VOC.</p> <p>No added Lead & Mercury.</p> <p>SIRIM Eco-label and Singapore Green Label certified.</p> <p>(*) Under test conditions. Dulux EasyClean Plus tested against 6 types of bacteria as per JIS Z 2801:2010 Antibacterial products – Test for antibacterial activity and efficacy to meet the anti-bacterial performance requirements for the following set of bacteria:</p> <ul style="list-style-type: none"> - Pseudomonas aeruginosa (ATCC 9027) - Staphylococcus aureus (ATCC 6538P) - Bacillus subtilis (ATC 6633) - Salmonella typhimurium (ATCC 14028) - MRSA (NCTC 12493) - Escherichia coli (ATCC 8739) <p>(**) Under test conditions. Effective against human coronavirus NL-63 (99% efficacy) - with 30 min of exposure on the painted surface (tested by IMSL lab UK).</p> <p>Virus and bacteria can also spread through other external/internal surfaces.</p>
PACK SIZE	1, 5 and 18 litres
COLOUR RANGE	Refer to Dulux colour catalogue

PERFORMANCE GUIDE

FILM PROPERTIES	
Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and able to withstand vigorous washing. Excellent scrubability and stain resistance (common household stains).
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 12m ² /litre.

PRODUCT DATA

COMPOSITION (nominal)	<p>Pigment : Lightfast Non-Lead Pigments and Mineral Extenders</p> <p>Binder : Acrylic Emulsion</p> <p>Solvent : Water</p>
VOLUME SOLIDS	White 41% (nominal), other colours will vary.



DULUX EASYCLEAN PLUS

SHEEN FINISH

WATER BASED

PRODUCT INFORMATION

APPLICATION

THINNING

Brush or Roller

For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).

Conventional Spray

Add up to 1 part of clean water to 5 parts of paint (20%)

Airless Spray

Ready for use

SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm² (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°

DRYING TIMES

Touch Dry

Single coat at standard thickness:
Dependant on temperature and humidity

Recoat

1-2 hours

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Dulux Sealer/Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 16%. These walls should be left to dry further.

SYSTEM INFORMATION

Powdery Surfaces

SEALER/PRIMER (1 COAT)

FINISH (MINIMUM 2 COATS)

Alkaline and/or New Surfaces

Dulux Weathershield Primer

Normal, Sound Surfaces

Dulux Exterior & Interior Wall Sealer

Dulux EasyClean Plus

Dulux Exterior & Interior Wall Sealer

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION

Product Safety Data Sheet available upon request

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties

ECP: 150421

Akzo Nobel Paints (Malaysia) Sdn Bhd
(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

AkzoNobel