



DULUX EASYCLEAN

MATT FINISH

WATER BASED

PRODUCT INFORMATION

PRODUCT NAME	Dulux EasyClean
PRODUCT CODE	A990 Line
DESCRIPTION	Dulux EasyClean is a premium interior quality matt finish paint that provides good stain resistance which allows you to clean common household stains off your wall easily. Now with Anti-bacterial functionality, it aids to inhibit the growth of bacteria on the walls. Formulated with Dulux Colourguard Technology, it locks in colours to keep your wall looking beautiful for longer.
USAGE	Dulux EasyClean is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement and wallboards.
BENEFITS	Good stain resistance with common household stains. Good washability. Anti-bacterial properties that aids to inhibit growth of bacterial on the walls. Colourguard technology that locks in the colour. Low Odour & Low VOC. No added Lead & Mercury. SIRIM Eco-label and Singapore Green Label certified.
PACK SIZE	1, 5 and 18 litres
COLOUR RANGE	Refer to Dulux colour catalogue

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and able to withstand moderate vigorous washing.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 12m ² /litre.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders Binder : Acrylic Emulsion Solvent : Water
VOLUME SOLIDS	White 35% (nominal), other colours will vary.

APPLICATION

THINNING Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%)
Conventional Spray Airless Spray	Add up to 1 part of clean water to 5 parts of paint (20%) Ready for use
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity 1-2 hours
CLEANING EQUIPMENT	Clean all equipment with water immediately after use.



DULUX EASYCLEAN

MATT FINISH
WATER BASED

PRODUCT INFORMATION

PRE-APPLICATION

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Dulux Sealer/Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 16%. These walls should be left to dry further.

SYSTEM INFORMATION

Powdery Surfaces
Alkaline and/or New Surfaces
Normal, Sound Surfaces

SEALER/PRIMER (1 COAT)

Dulux Weathershield Primer
Dulux Exterior & Interior Wall Sealer
Dulux Exterior & Interior Wall Sealer

FINISH (MINIMUM 2 COATS)

Dulux EasyClean

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION

Product Safety Data Sheet available upon request

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties

EC: 010321

Akzo Nobel Paints (Malaysia) Sdn Bhd
(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

AkzoNobel