



DULUX INSPIRE INTERIOR GLOW

DULUX INSPIRE INTERIOR GLOW (Waterbased)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Inspire Interior Glow
DESCRIPTION	Dulux Inspire Interior Glow contains advanced Chroma Brite Glow Technology to give long lasting stunning bright walls compared with regular paint. It also provides good coverage to deliver a smooth finish. With Dulux Inspire Interior Glow, your home will always look stunningly bright and shine longer.
USAGE	Dulux Inspire Interior is suitable for all normal interior wall and ceiling surfaces.
BENEFITS	Attractive high-sheen finish. Good coverage
PACK SIZE	1, 5 and 18 litres
COLOR RANGE	See Dulux Inspire Colour Catalogue.

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing. Not suitable where frequent heavy condensation is likely, as in kitchens and bathrooms.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10 - 11 m ² /L.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Copolymer Emulsion. Solvent : Water.
VOLUME SOLIDS	White 34% (nominal), other colours will vary.

APPLICATION

THINNING Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 10 parts of paint (10%). For normal use thinning is usually not necessary.
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
Airless Spray	Ready for use. Thinning is usually not required.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Depends on temperature and humidity. 2-3 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These wall should be left to dry further.
----------------------------	---

PRE-APPLICATION

SYSTEM INFORMATION

Old and Powdery Surfaces

PRIMER (1 COAT)

Dulux Adhesion Promoting Interior
Wall Primer (A579-15458)

FINISH (2 COATS)

Dulux Inspire Interior Glow
(* Vibrant / deep shades may
require additional coats)

New and Normal Surfaces

Dulux Exterior & Interior Wall Sealer
(A1290013 0015527)

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION

- Refer to "Dulux Product Safety Data Sheet" for further details.
- In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Issued Date | 10 2018

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

A BRAND FROM
AkzoNobel