

DULUX AMBIANCE™ VELVET



PRODUCT INFORMATION

Description	Dulux Ambiance™ Special Effects Paints include the finest featured finishes and textures to create endless unique combinations to personalise your world. Dulux Ambiance™ Velvet is inspired by smooth and sleek fabrics, draping your walls with a rich velvet finish to give them a timeless look and feel.
Benefits	<ul style="list-style-type: none">· Ready-to-use, trowel applied emulsion paint· Velvety finish, colour changing effect, textile effect depending on required effect and angle of light incident, way of application.· Optimized rheology and open time for better application and flow & levelling
Usage	Ideal for new and previously painted interior masonry, plaster, and building boards surfaces.
Pack Size	Available only in 1 Liter pack (refer to the pack for the fill volume)
Colour Range	See appropriate Colour Card.

PHYSICAL FILM PROPERTIES

Water Resistance	Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.
-------------------------	--

PRODUCT DATA

Composition	Pigment: Light-fast Non-Lead/Chrome pigment Binder: Waterborne Polymer Solvent: Water
Drying Times Touch Dry Hard Dry	Single coat at standard thickness: 1-2 hours 4-6 hours Drying time may vary according to temperature and humidity.
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity up to 6 m ² / L / coat
Type Of Finishing	Velvety finish

DULUX AMBIANCE™ VELVET



APPLICATION GUIDE

Surface Preparation

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose and defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush. Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Treat any areas affected mould, lichens, algae and moss with fungicidal treatment/ Dulux Fungicidal Wash. Repair any surface defects with an appropriate filler. Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Primer (see below System Recommendation). Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust. Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.

Application tools

Trowel or roller along with trowel

Dilution

Ready to use . No dilution

Recommended Application Condition

- Dulux Ambiance™ Velvet is recommended for interior walls only.
- Avoid windy conditions in the room.
- Room temperature should ideally be between 20°C and 35°C.
- Very hot, dry conditions are to be avoided.
- Use of any other paint apart from the specially formulated Dulux Ambiance™ Velvet may deviate from the desired finish and make it hard to recondition.

Prime

Prime surface with a coat of appropriate Dulux Sealer first.

-Topcoat

Apply 2 coats of Dulux Ambiance™ Pearl Glo tinted in required colour. Please ensure 2 -4 hours drying time between coats.

Dulux Ambiance™ Velvet

Apply 1st coat of Dulux Ambiance™ Velvet in required colour with roller and then use trowel to smoothen out the paint. For the 2nd coat, apply a thin layer of paint in waves by trowel. Ensure 4 -6 hours drying time between coats. This effect finish is not washable. Please use dry cloth to clean the wall if needed.

System recommendation

System Information	Sealer (1 coat)	Topcoat (2 coats)	Special Effect (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Dulux Sealer (solvent-based)		
<i>New Surfaces</i>	Dulux Sealer (water-based)	Dulux Ambiance™ Pearl Glo	Dulux Ambiance™ Velvet
<i>Normal, Sound Surfaces</i>	No sealer required		

For alternative coating systems, please refer to our Sales Representative

Cleaning Up

Clean all equipment with clean water immediately after use.

DULUX AMBIANCE™ VELVET



HEALTH, SAFETY & ENVIRONMENT INFORMATION

Please refer to Product Safety Data Sheet

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

Customer Care Department

Tel: 1-800-88-9338

Website: www.dulux.com.my

Email: customercare.my@akzonobel.com

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.