

CLEAR PROOF INTERIOR GLOSS



PRODUCT NAME Clear Proof Interior Gloss

PRODUCT CODE CGLVAR

DESCRIPTION Taubmans Clearproof Interior Gloss varnish is a solvent based wood finish

USAGE Suitable for use on all types of new or previously treated interior soft and hard woods. Typical uses include parquet floors, panelling, cane or wood furniture, doors and partitions

BENEFITS
Excellent abrasion resistance
Exhibit fast drying properties
Highlights the natural beauty of the grain of the wood.

PACK SIZE 1 and 5 Litres

COLOUR RANGE Clear only

FILM PROPERTIES

Chemical Resistance Resist alcohols and aliphatic hydrocarbons. Film is liable to attack from other strong solvents

Heat Resistance Resistant up to 90°C

Water Resistance Resistant to the moisture level experienced during mopping. Not suitable if there is water ponding.

THEORETICAL COVERAGE A guide to the theoretical coverage which can be achieved under normal conditions is 14m²/L

COMPOSITION (nominal)
Pigment: Lightfast Non-Lead Pigments
Binder: Polyurethane Alkyd
Solvent: White spirit.

VOLUME SOLIDS 38% (nominal)

FLASH POINT 38-55°C

DRYING TIME
Single coat at standard thickness:
Touch Dry 1-2Hours
Recoat 3 hours

FILM THICKNESS
Wet: 50 micro-meters
Dry: 20 micro-meters

SURFACE PREPARATIONS

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease wax etc. All surfaces should be thoroughly rubbed down in the direction of the grain, using a suitable abrasive paper and then dusted off.

APPLICATION

Brush & Roller

**THINNING**

Brush or Roller

For sealing new or bare surfaces, thin up to 1 part of Mineral Turpentine to 5 parts of paint (20%).
For normal use, thinning is usually not necessary

STIR

Stir paint in a circular lifting motion to mix well before use

SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment.

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm² (2000 lb./sq. in) with a spray tip size 0.38mm (13 thou) and a spray tip angle of 65°.

CLEAN UP

Clean all equipment with Mineral turpentine immediately after use.

MAINTENANCE

To remove oil or grease from coated surface use degreaser. For most spillages simply clean with detergent and hose or mop away with fresh water.

SYSTEM INFORMATION**PRIMER/ SEALER/UNDERCOAT****FINISH (2 COATS)**

Clearproof Sanding Sealer

Clearproof Interior Gloss Varnish

**SAFETY HEALTH AND
ENVIRONMENT INFORMATION**

Refer Safety Data Sheet -available for use on request

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock

AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03, Fax: +675 7031 8440/8441
Vakari Street, Gerehu Stage 6, Port Moresby,
Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)