


Clear Proof Sanding Sealer

PRODUCT NAME	Clear Proof Sanding Sealer
PRODUCT CODE	INSAND
DESCRIPTION	Clear Proof Interior sanding sealer is a Taubmans modified alkyd based sanding sealer for interior woodwork.
USAGE	Suitable for use on bare or stained interior timber surfaces prior to finishing.
BENEFITS	<p>Excellent abrasion resistance.</p> <p>Exhibits fast-drying properties.</p> <p>Excellent brush/roller loading.</p> <p>Excellent durability, sand-ability and fungus resistance.</p> <p>Lead free formulation – Non-toxic.</p> <p>Gloss level is flat (0-1%).</p> <p>Highlights the natural beauty of the grain of the wood.</p>
PACK SIZE	5 Litres
COLOUR RANGE	Clear only
FILM PROPERTIES	
Chemical Resistance	Resists alcohols and aliphatic hydrocarbons. Film is liable to attack from other strong solvents.
Heat Resistance	Resistant up to 90°C.
Water Resistance	Resistant to the moisture level experienced during mopping. Not suitable if there is water ponding.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10 m ² /L.
COMPOSITION (nominal)	<p>Pigment: Lightfast Non Lead Pigments.</p> <p>Binder: Polyurethane Alkyd.</p> <p>Solvent: White Spirit.</p>
VOLUME SOLIDS	38% (nominal)
FLASH POINT	32-55°C
DRYING TIME	Single coat at standard thickness:
Touch Dry	1-2 hours.
Recoat	3 hours
FILM THICKNESS	<p>Wet: 50 micro-meters</p> <p>Dry: 20 micro-meters</p>
SURFACE PREPARATIONS	Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. All surfaces should be thoroughly rubbed down in the direction of the grain, using a suitable abrasive paper and then dusted off.

APPLICATION	Brush 	
THINNING	For sealing new or bare surfaces thin up to 1 part of Mineral Turpentine to 5 parts of paint (20%).	
Brush	For normal use thinning is usually not necessary.	
STIR	Stir paint in a circular lifting motion to mix well before use	
CLEAN UP	Clean all equipment with Mineral Turpentine immediately after use.	
MAINTENANCE	To remove oil or grease from coated surface use degreaser. For most spillages clean immediately with Mineral Turpentine.	
SYSTEM INFORMATION	PRIMER/ SEALER/UNDERCOAT	FINISH (2 COATS)
	NA	Clear Proof Interior Sanding Sealer (INSAND)
SAFETY HEALTH AND ENVIRONMENT INFORMATION	Refer Safety Data Sheet -available for use on request	

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock

AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03, Fax: +675 7031 8440/8441
Vakari Street, Gerehu Stage 6, Port Moresby,
Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)