

Easycoat Low Sheen

PRODUCT NAME	Easycoat (water-base)
VARIANT NAME	Low Sheen
DESCRIPTION	A premium quality highly durable and washable finish.
USAGE	Suitable for all normal interior wall and ceiling surfaces. For use in areas subject to frequent or heavy condensation as in some kitchens and bathrooms. Suitable for use on timber or wooden surfaces.
BENEFITS	Formulated with: Tough Mineral Technology to offer tough resilient surface that is washable and easy cleaning Colour guard Technology to lock colours in. Antibacterial protection Low odour and VOC Smooth Finish
PACK SIZE	1, 5, 18 Litres
COLOUR RANGE	Refer to Taubmans Colour Offer
FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand vigorous washing. Excellent scrub ability and stain resistance. Extremely hardwearing and excellent adhesion.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal condition is 13 m ² /liter
RECOMMENDATIONS	Not recommended for areas exposed to flame or high heat.
COMPOSITION (nominal)	Pigment: Lightfast Non-Lead Pigments Binder: Acrylic Emulsion. Solvent: Water
VOLUME SOLIDS	White 41%, other colors will vary
FLASH POINT	Non-Flash
DRYING TIME Touch Dry	Single coat at standard thickness: Dependant on temperature and humidity.
Recoat	1-2 hours. Allow 4 hours in cold or humid areas
FILM THICKNESS	<30µm
	Surfaces must be sound, clean, dry and free from all defective or poorly

SURFACE PREPARATIONS

adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with fungicidal wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.

APPLICATION

Brush & Roller

**THINNING**

For normal use, thinning is usually not necessary. If required, add up to 1 part of clean water to 10 parts of paint (10%).

Conventional Spray

Add up to 1 part of clean water to 10 parts of paint (10%).

Airless Spray

Add up to 1 cup of clean water to 10 parts of paint (10%)

SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment.

FINISH (2 COATS)

Taubmans Easycoat Low Sheen

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm² (2000 lb./sq. in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.

Taubmans Easycoat Low Sheen

Taubmans Easycoat Low Sheen

CLEAN UP

Clean all equipment with clean water immediately after use.

MAINTENANCE

To remove oil or grease from coated surface use degreaser. For most spillages simply clean with detergent and hose or mop away with fresh water.

SYSTEM INFORMATION**UNDERCOAT (1 Coat)****FINISH (2 Coats)**

Plaster Board

Ultra Kote Acrylic Sealer Undercoat

Easycoat Low Sheen

Masonry

Taubmans 3 in 1 or Ultra Kote Acryl Sealer U/coat

Easycoat Low Sheen

Previously painted Surface

Ultra Kote Acrylic Sealer Undercoat

Easycoat Low Sheen

SAFETY HEALTH AND ENVIRONMENT INFORMATION

Refer to Product Safety Data Sheet –available for use on request.

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock

AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03, Fax: +675 7031 8440/8441
Vakari Street, Gerehu Stage 6, Port Moresby, Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)