

EASYCOAT SEMI-GLOSS

PRODUCT NAME	Easycoat Semi-Gloss
VARIANT NAME	Semi-Gloss
DESCRIPTION	Easycoat Semi-Gloss is a premium quality, highly durable and washable finish.
USAGE	Easycoat Semi-Gloss is suitable for all normal interior wall and ceiling surfaces. For use in areas subject to frequent or heavy condensation as in some kitchens and bathrooms. For use on timber or wooden surfaces.
BENEFITS	Highly washable paint film and easy cleaning Gives an attractive mid sheen pearl-smooth finish Low Odour and VOC Lead-free;-non toxic Colour guard Technology to lock colours in
PACK SIZE	1, 5, 18 Litres
COLOUR RANGE	Refer to Taubmans Colour Offer
FILM PROPERTIES	
Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10.5-11.5 m ² /liter.
COMPOSITION (nominal)	Pigment: Lightfast Non-Lead Pigments and Mineral Extenders. Binder: PVA Copolymer Emulsion. Solvent: Water.
VOLUME SOLIDS	White 35% (nominal), other colours will vary
FLASH POINT	Non-Flash
DRYING TIME	Single coat at standard thickness:
Touch Dry	Dependant on temperature and humidity.
Recoat	1-2 hours. Allow 4 hours in cold or humid areas
FILM THICKNESS	<30µm
SURFACE PREPARATIONS	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. If after thorough

preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below).

APPLICATION

Brush & Roller



THINNING

Brush or Roller

For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%).

Conventional Spray

For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).
Add up to 1 part of clean water to 5 parts of paint (20%).

Airless Spray

Ready for use.

STIR

Stir paint in a circular lifting motion to mix well before use

PRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment.

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm² (2000 lb./sq. in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.

CLEAN UP

Clean all equipment with clean water immediately after use.

MAINTENANCE

To remove oil or grease from coated surface use degreaser. For most spillages simply clean with detergent and hose or mop away with fresh water.

SYSTEM INFORMATION

UNDERCOAT (1 COAT)

FINISH (2 COATS)

Plaster Board

Ultra Kote Acrylic Sealer Undercoat

Easycoat Semi-Gloss (ESABSA)

Masonry

Ultra Kote Acrylic Sealer Undercoat

Easycoat Semi-Gloss (ESABSA)

Previously Painted Surface

Ultra Kote Acrylic Sealer Undercoat

Easycoat Semi-Gloss (ESABSA)

SAFETY HEALTH AND ENVIRONMENT INFORMATION

Refer Safety Data Sheet-available for use on request

Any advice, recommendations, information, assistance or service provided by ICI Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by ICI Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock
AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03,
Fax: +675 7031 8440/8441
Vakari Street,
Gerehu Stage 6,
Port Moresby,
Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)