


Prep Right 3 in 1 Primer

PRODUCT NAME	Prep Right 3 in 1 primer
CODE	UPASPU
DESCRIPTION	Taubmans 3-IN-1 is high performance water based all-purpose primer, sealer and undercoat with outstanding hiding, filling and sanding properties suitable for use on both Interior/ Exterior surfaces. Taubmans 3-IN-1 is rapid drying with fast recoat and features "no mess" application- reducing masking and clean-up.
USAGE	Interior surfaces as an undercoat directly over bare timber, as a sealer for wallboards (e.g. paper faced plasterboard), or as a primer for galvanized steel. Taubmans 3-in-1 is particularly recommended for repaint over aged enamel to provide a sound bond for other water based topcoats. Suitable for Exterior application when used as a primer for timber or on previously painted surfaces. Taubmans 3-in-1 can also be used in "high humidity" areas such as bathrooms, laundries, kitchens, etc. under both water based finishes and oil based enamels.
BENEFITS	<p>Taubmans 3-in-1 conforms to Singapore Green label criteria and also has excellent adhesion properties and rust prevention properties.</p> <p>100% water-based</p> <p>Fast drying</p> <p>Suitable for use on wood and metal surfaces.</p> <p>Enhance adhesion.</p> <p>Enhance smoothness</p> <p>Low Odor</p> <p>Singapore Green Label certified</p>
PACK SIZE	1, 5, 18 Litres
COLOUR RANGE	White only (tinting not recommended)
FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal environments.
THEORETICAL COVERAGE	Theoretical coverage which can be achieved under normal conditions is up to 16m ² /L. Coverage will be lower on rough or absorbent surfaces.
COMPOSITION (nominal)	<p>Pigment: Non-Lead Pigments.</p> <p>Binder: Styrene Acrylic</p> <p>Solvent: Water</p>
VOLUME SOLIDS	45%
FLASH POINT	Non-Flash
DRYING TIME Touch Dry Recoat	<p>The required number of coats is two. Ensure adequate ventilation.</p> <p>30 minutes</p> <p>2 hours at 25°C. Allow 4 hours in cold or humid areas.</p>
FILM THICKNESS	<20µm
SURFACE PREPARATIONS	Surface preparation for New Work: Surfaces must be clean and dry before painting. Dust down bare wallboards and interior timber. New concrete and cement render must be allowed to cure for 28 days before painting. Weathered timber must be sanded back

	to a sound surface. Repaint Remove all loose and flaking paint. Sand to feather edges before painting. Remove surface chalk and powder, dirt, oil and grease. Spot bare areas with Taubmans 3-in-1 before applying a full coat. Do not use 3-in-1 on set plaster, fibrous plaster or plaster glass.	
APPLICATION	Brush & Roller 	Apply one coat using a brush or roller. Keep brushes and roller working freely by occasionally rinsing in water. A 10mm regular nap cover or similar will give best results.
THINNING Brush or Roller	For normal use, thinning is usually not necessary. If required, dilute with 10% clean water and stir well before use.	
STIR	Stir paint in a circular lifting motion to mix well before use	
SPRAY RECOMMENDATIONS	Satisfactory through most equipment. A typical set up for spray application would be a minimum working Pressure on paint of 140Kg/cm ² (2000lb/sq. in) with a spray tip size 0.58mm (23thou) and a spray tip angle 65°. Dilute up to 10% of water (Maximum)	
Conventional Spray		
Airless Spray	Ready for use	
CLEAN UP	Clean all equipment with clean water immediately after use.	
MAINTENANCE	To remove oil or grease from coated surface use degreaser. For most spillages simply clean with detergent and hose or mop away with fresh water.	
SYSTEM INFORMATION	Primer/ Sealer/Undercoat	FINISH (2 COATS)
Metal/ Wood Surfaces	Taubmans 3 in 1	Any Taubmans top coat Products -Easycoats -Sunproof -Ultra-Kote
SAFETY HEALTH AND ENVIRONMENT INFORMATION	Refer Safety Data Sheet -available for use on request	

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock

AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03, Fax: +675 7031 8440/8441
Vakari Street, Gerehu Stage 6, Port Moresby,
Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)