


Ultra-Kote Interior Semi-Gloss Acrylic

PRODUCT NAME	Ultra-Kote Interior Semi-Gloss Acrylic
CODE	ULKSGLA
DESCRIPTION	Ultra Kote Interior Semi-Gloss Acrylic is a mid-tier quality, highly durable and washable emulsion with a mid-sheen finish.
USAGE	Ultra-Kote Interior Semi-Gloss Acrylic is suitable for all normal interior wall and ceiling surfaces.
BENEFITS	Smooth Finish Low odour and VOC Lead-free formulation –Non toxic
PACK SIZE	5, 18 Litres
COLOUR RANGE	Refer to Ultra-Kote Colour Range
FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10.5-11.5 m2/litre. Coverage will be lower on rough or absorbent surfaces..
COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : PVA Copolymer Emulsion. Solvent : Water.
VOLUME SOLIDS	White 35% (nominal)
FLASH POINT	Non-Flash
DRYING TIME Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 1-2 hours. (Allow 4 hours in cold or humid areas).
FILM THICKNESS	<20µm
SURFACE PREPARATIONS	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below).
APPLICATION	Brush & Roller 
THINNING Brush or Roller Conventional Spray Airless Spray	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%). Add up to 1 part of clean water to 5 parts of paint (20%). Ready for use.

STIR

Stir paint in a circular lifting motion to mix well before use

SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment.

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm² (2000 lb/sq. in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.

CLEAN UP

Clean all equipment with clean water immediately after use.

MAINTENANCE

To remove oil or grease from coated surface use degreaser. For most spillages simply clean with detergent and hose or mop away with fresh water.

SYSTEM INFORMATION

Primer/ Sealer/Undercoat

FINISH (2 COATS)

Plaster Board

Ultra Kote Acrylic Sealer Undercoat

Ultra Kote Interior Acrylic Semi-Gloss

Masonry

Ultra Kote Acrylic Sealer Undercoat

Ultra Kote Interior Acrylic Semi-Gloss

Previously Painted Surface

Ultra Kote Acrylic Sealer Undercoat

Ultra Kote Interior Acrylic Semi-Gloss

**SAFETY HEALTH AND
ENVIRONMENT INFORMATION**

Refer Safety Data Sheet -available for use on request

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties. For further information or if you have any concerns about using this product, kindly contact:

Attn: Stephen Woodcock

AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03, Fax: +675 7031 8440/8441
Vakari Street, Gerehu Stage 6, Port Moresby,
Papua New Guinea

Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)