

# DULUX SEALER (SOLVENT-BASED)



<b>Product Name</b>	Dulux Sealer (solvent-based)
<b>Product Code</b>	A579-15054
<b>Usage</b>	Dulux Sealer (solvent-based) is a solvent-based sealer for interior and exterior masonry surfaces such as brickwork, plaster, cement and textured walls. It is suitable for use on both new and previously painted surfaces.
<b>Pack Size</b>	1, 5 and 20 litres
<b>Colour Range</b>	White only
<b>Film Properties</b>	
<i>Water Resistance</i>	Will tolerate a slightly damp surface but is not suitable where the surface is saturated.
<b>Composition (nominal)</b>	Pigment : Tioxide Binder : Vinyl-toulene acrylate co-polymer Solvent : White Spirit
<b>Volume Solids</b>	30%
<b>Drying Times</b>	Single coat at standard thickness :
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	4 - 5 hours
<b>Film Thickness</b>	Wet : 110 micro-metres Dry : 30 micro-metres
<b>Theoretical Coverage</b>	Theoretical coverage which can be achieved under normal conditions is 8-10 m <sup>2</sup> /litre.
<b>Application</b>	
<b>Thinning</b>	
<i>Brush or Roller</i>	If required for sealing new or bare surfaces thin up to 1 part of Dulux Thinner 850-41 or white spirit to 10 parts of paint (10%). For normal use thinning is not usually necessary.
<i>Conventional Spray</i>	Add up to 1 part of Dulux Thinner 850-41 or white spirit to 10 parts of paint (10%).
<i>Airless Spray</i>	Ready for use.
<b>Spraying Recommendations</b>	
<i>Conventional Spray</i>	Satisfactory through most equipment.

# DULUX SEALER (SOLVENT-BASED)



<i>Airless Spray</i>	A typical set up for spray application would be a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.43mm (17 thou) and a spray tip angle 65°.	
<b>Cleaning Up</b>	Clean all equipment with Dulux Thinner 850-41 or white spirit immediately after use.	
<b>Surface Preparation</b>	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Remove all loose paint or powdery residue by brushing/scraping with a stiff fibre brush or high pressure water jet. Treat area affected by mould, lichens, algae and moss with Dulux Fungicidal Wash.	
<b>System Information</b>	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Dulux Sealer (solvent-based)	Dulux Pure OR Dulux All
<i>New Surfaces</i>	Dulux Sealer (water-based) OR Dulux Supercoat Alkali Resisting Primer Sealer	OR Dulux Wash & Wear OR Dulux Pentelite OR Dulux Weathershield
<i>Normal, Sound Surfaces</i>	No sealer required	
	Note: This sealer may also be used with wide range of other Dulux Decorative Paint Systems.	
<b>Health, Safety and Environment Information</b>	Product Safety Data Sheet available upon request.	

**For further information or if you have any concerns about using this product, contact us at:**

**Akzo Nobel Paints (Singapore) Pte Ltd**  
AkzoNobel House, 3 Changi Business Park Vista  
#05-01, Singapore 486051  
Tel: (65) 6265 0677 Fax: (65) 6265 4775  
Email: customer.care.sg@akzonobel.com  
Emergency hotline: (65) 6336 7608

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.