

DULUX SEALER (WATER-BASED)



Product Name	Dulux Sealer (water-based)
Product Code	A931-1050
Usage	Dulux Sealer (water-based) is a high quality styrene acrylic water-based sealer for interior and exterior masonry surfaces such as brickwork, plaster, cement and textured walls. It is suitable for use on both new and previously painted surfaces. Dulux Sealer (water-based) conforms to the Singapore Green Labelling Scheme (032-038-0506).
Pack Size	5 and 20 litres
Colour Range	White only
Film Properties	
<i>Water Resistance</i>	Will tolerate damp surface but is not suitable where the surface is saturated. Note: It is best to dry substrate to protimeter reading of below 15% before application of sealer.
Composition (nominal)	Pigment : Lightfast Non-lead Pigments Binder : Styrene Acrylic Copolymer Emulsion Solvent : Water
Volume Solids	45%
Drying Times	Single coat at standard thickness :
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	2 - 4 hours
Film Thickness	20 - 30 microns dry film thickness
Theoretical Coverage	Theoretical coverage which can be achieved under normal conditions is 11m ² /litre.
Application	
Thinning	
<i>Brush or Roller</i>	Ready for use.
<i>Conventional Spray</i>	Add up to 1 part of clean water to 10 parts of paint (10%).
<i>Airless Spray</i>	Ready for use.
Spraying Recommendations	
<i>Conventional Spray</i>	Satisfactory through most equipment.

DULUX SEALER (WATER-BASED)



<i>Airless Spray</i>	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.58 mm (23 thou) and a spray tip angle 65°.	
Cleaning Up	Clean all equipment with clean water immediately after use.	
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Dulux Fungicidal Wash.	
System Information <i>Powdery and Alkaline Surfaces</i> <i>New Surfaces</i> <i>Normal, Sound Surfaces</i>	Sealer (1 coat) Dulux Sealer (solvent-based) Dulux Sealer (water-based) No sealer required	Finish (2 coats) Dulux Pure OR Dulux All OR Dulux Wash & Wear OR Dulux Pentalite Note: This sealer may also be used with wide range of other Dulux Decorative Paint Systems.
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.	

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Paints (Singapore) Pte Ltd
 AkzoNobel House, 3 Changi Business Park Vista
 #05-01, Singapore 486051
 Tel: (65) 6265 0677 Fax: (65) 6265 4775
 Email: customer.care.sg@akzonobel.com
 Emergency hotline: (65) 6336 7608

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.