


DULUX SOLARSCREEN



Product Name	Dulux Solarscreen
Product Code	A339-Line
Usage	Dulux Solarscreen is a durable pigmented varnish based on a special resin for the decoration and protection for all types of new or previously painted wood surfaces. It has excellent abrasion resistance and highlights the natural beauty of the grain of the wood. It is water resistant and has a flexible finish that provides long lasting protection. Its unique formulation filters out UV rays thereby minimising the traditional problems of cracking, flaking and peeling.
Pack Size	1 and 5 litres
Colour Range	See appropriate Colour Card
Composition (nominal)	Pigment : Lightfast Non-lead Pigments Binder : Modified Alkyd Solvent : White Spirit
Volume Solids	38%
Drying Times	Single coat at standard thickness : <i>Touch Dry</i> 1 - 2 hours <i>Recoat</i> 4 hours
Film Thickness	Wet : 50 micro-metres Dry : 20 micro-metres
Theoretical Coverage	Theoretical coverage which can be achieved under normal conditions is 19 m ² /litre.
Application	
Thinning	<i>Brush or Roller</i> For sealing new or bare surfaces thin with up to 1 part of Dulux Thinner 850-41 or white spirit to 5 parts of paint (20%). For normal use thinning is not usually necessary.
Cleaning Up	Clean all equipment with Dulux Thinner 850-41 or white spirit immediately after use.
Surface Preparation	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable paper working in the direction of the woodgrain and dusted off. Clean all dirt, mould, algae or lichen with a wire brush. Treat areas affected by fungi or algae with Dulux Fungicidal Wash.

DULUX SOLARSCREEN



System Information	Primer N.A.	Finish (3 coats) Dulux Solarscreen
Flash Point	32°C	
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.	

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Paints (Singapore) Pte Ltd
AkzoNobel House, 3 Changi Business Park Vista
#05-01, Singapore 486051
Tel: (65) 6265 0677 Fax: (65) 6265 4775
Email: customer.care.sg@akzonobel.com
Emergency hotline: (65) 6336 7608

Any advice, recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.