


DULUX TIMBERCOLOUR



Product Name	Dulux Timbercolour
Product Code	A926-Line
Usage	Dulux Timbercolour is a low sheen water based acrylic paint ideal for direct application to exterior wood surfaces including fences, barge-boards, facias, exposed balconies, wood walls and cladding. It contains light-fast pigments and an effective mould control additive. It has excellent durability and good adhesion.
Pack Size	5 litres
Colour Range	See appropriate Colour Card
Film Properties	
<i>Water Resistance</i>	Will tolerate the levels of atmospheric humidity present in normal exterior environments.
Composition (nominal)	Pigment : Lightfast Non-lead Pigments Binder : Acrylic Emulsion Solvent : Water
Volume Solids	35% (nominal)
Drying Times	Single coat at standard thickness :
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	2 - 3 hours
Film Thickness	30 - 40 microns dry film thickness
Theoretical Coverage	Theoretical coverage which can be achieved under normal condition is 10 - 11 m ² /litre.
Application	
Thinning	
<i>Brush or Roller</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%)
Cleaning Up	Clean all equipment with clean water immediately after use.
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper working in the direction of the grain and dusted off. Clean off all dirt, mould, algae, lichen or moss with a wire brush. Treat areas affected by fungi or algae with Dulux Fungicidal Wash.

DULUX TIMBERCOLOUR



System Information	Primer N.A.	Finish (2-3 coats) Dulux Timbercolour
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.	

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Paints (Singapore) Pte Ltd
AkzoNobel House, 3 Changi Business Park Vista
#05-01, Singapore 486051
Tel: (65) 6265 0677 Fax: (65) 6265 4775
Email: customer.care.sg@akzonobel.com
Emergency hotline: (65) 6336 7608

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.