


# DULUX WATER BASED GLOSS PRIMER



<b>Product Name</b>	Dulux Water-Based Gloss Primer
<b>Usage</b>	Dulux Water-Based Gloss Primer is a water-based innovation specially designed for application on wood and metal surfaces. It is based on a 100% water-based acrylic system. The product has low odour and low VOC, and is quick drying.
<b>Benefits</b>	100% water-based Fast drying Low VOC, low odour Enhanced smoothness Enhanced adhesion No added lead & mercury Singapore Green Label certified
<b>Finish</b>	Matt
<b>Colour</b>	White
<b>Pack Size</b>	1 and 5 litres
<b>Composition (nominal)</b>	Pigment : Non-Lead Pigments and Mineral Extenders Binder : Acrylic Emulsion Solvent : Water
<b>Drying Times</b>	For single wet coat applied: <i>Touch Dry</i> 30mins - 1 hour under normal conditions <i>Recoat</i> 1 - 3 hours under normal conditions
<b>Theoretical Coverage</b>	Approximate practical coverage up to 14m <sup>2</sup> /litre/coat by brush application. Approximate values only and may vary depending on application conditions, application tools used and substrate.
<b>Application</b>	 * Only apply with Small Smooth Roller or Brush for best results.
<b>Cleaning Up</b>	Clean all equipment with water after use.

# DULUX WATER BASED GLOSS PRIMER

---



**Surface  
Prepara  
tion**

**New wood:**

Surface must be dry, clean, and free from all defects, or poorly adhering materials, dirt, grease, wax, etc.

Recommend to smoothening surface before painting. If necessary, sand with an abrasive paper to a smooth and even surface then remove any dust before painting.

**Previously-painted wood:**

If previous paint is in a good condition, sand with abrasive paper for good adhesion of new paint. If previous paint is damaged, remove flaking or peeling areas until the wood surface can be reached.

Remove all contaminants. Sand with an abrasive paper to a smooth and even surface then remove any dust before painting.

**New metal:**

Surface must be dry, clean, and free from all defective, or poorly adhering materials, dirt, grease, wax, and corrosive, etc. Remove oil or other contaminants with a suitable solvent. Let the

# DULUX WATER BASED GLOSS PRIMER



solvent dry before painting. If necessary, sand with an abrasive paper to a smooth and even surface then remove any dust before painting.

**Previously-painted metal:**

If previous paint is in a good condition, sand with an abrasive paper for good adhesion of new paint. If surface is defective or corrosive, thoroughly sand until previous paint and/or corrosive is completely removed.

Caution: Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**System Information**

Primer (1 coat)	Finish (2 coats)
-----------------	------------------

# DULUX WATER BASED GLOSS PRIMER



Wood & Metal Surfaces	Dulux Water-Based Gloss Primer	Dulux Water-Based Gloss
-----------------------	--------------------------------	-------------------------

Health, Safety and Environment Information	Product Safety Data Sheet available upon request.
--	---

For further information or if you have any concerns about using this product, contact us at:

<b>Akzo Nobel Paints (Singapore) Pte Ltd</b> AkzoNobel House, 3 Changi Business Park Vista #05-01, Singapore 486051 Tel: (65) 6265 0677 Fax: (65) 6265 4775 Email: customer.care.sg@akzonobel.com Emergency hotline: (65) 6336 7608	Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application
---	---

# DULUX WATER BASED GLOSS PRIMER



n is given  
in good  
faith.  
However,  
advice,  
recommen-  
dations,  
informati-  
on,  
assistan-  
ce or  
service  
provided  
by  
AkzoNob-  
el Paints  
is  
provided  
without  
expresse-  
d or  
implied  
warrantie-  
s.