

# WEATHERSHIELD QUICK DRY EXTERIOR GLOSS

**Weathershield** Quick Dry Exterior Gloss from **Dulux Trade** is a water-based gloss finish which is part of a paint system specially developed to give long lasting protection to exterior wood. The **Weathershield** Quick Dry Exterior Gloss system will provide extensive protection for up to six years if correctly applied as per the instructions for use. Contains a fungicide to inhibit mould growth on the paint film and help it stay cleaner for longer.

## KEY BENEFITS

- 6 Year All Weather Protection
- Tough & Durable Protection
- Coverage up to 16m<sup>2</sup> per litre

## PRODUCT INFORMATION

### Typical Use

Ideal for use on exterior woodwork, primed metal and plastic.

### Pack Size

1L, 2.5L and 5L.

### Colour Range

See appropriate **Dulux Trade** colour literature or visit [duluxtrade.co.uk](http://duluxtrade.co.uk).

### Film Thickness

*Film thickness will be dependent on the coverage achieved.*

**Wet:** 45 microns.

**Dry:** 25 microns.

### Composition (nominal)

**Pigment:** Lightfast Pigments.

**Binder:** Acrylic Copolymer Emulsion.

**Solvent:** Water.

### Volume Solids

White: 34% (nominal). Other colours will vary.

## SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Treat any knots in wood with an appropriate knotting solution. Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**. Prime any bare metal with 1 coat of **Dulux Trade Metal Primer**.

When painting areas such as plastic rainwater goods, **Weathershield** Quick Dry Exterior Gloss can be used. Apply 1 coat of **Weathershield** Quick Dry Exterior Gloss thinned to 1 part water to 10 parts paint direct to the surface.

New joinery is often factory primed using a stain basecoat (also called a dual-purpose primer). These materials quickly erode when left exposed and may need to be re-primed.

## SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE.

Prime all bare wood with 2 coats of **Weathershield Preservative Primer**\*, followed by 1 coats of the appropriate coloured **Weathershield** Quick Dry Exterior Undercoat. Finish with 2 coats of **Weathershield** Quick Dry Exterior Gloss.

Where a special process colour is to be used or a strong colour change is required, additional coats will be required (see appropriate **Dulux Trade** colour card).

Allow a minimum of 2 hours before overcoating **Weathershield** Quick Dry Exterior Undercoat. Allow up to 4 hours before applying a second coat of **Weathershield** Quick Dry Exterior Gloss.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

When painting resinous wood or woodwork with a history of blistering it is advisable to use light colours only, particularly on south facing elevations. The maximum benefits of this system



# WEATHERSHIELD QUICK DRY EXTERIOR GLOSS

534

will only be realised when used as directed above on good quality timber that conforms to BS EN 942: 1996, in conjunction with good component design.

## APPLICATION METHOD

Brush only. Do not spray.  
Do not apply in temperatures below 10°C or outside where there is a likelihood of rain, fog or frost.

### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m<sup>2</sup> per litre.

### Thinning

This product should not be thinned.

### Spray Recommendations

This product should not be sprayed.

### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 2 hours.

**Recoat:** 4 hours.

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:0333 222 70 70).

\* **Weathershield** Preservative Primer<sup>™</sup> contains 3-iodo-2-propynyl-n-butyl carbamate and propiconazole.  
**Use biocides safely. Always read the label and product information before use.**

**Always read full Health, Safety & Environmental Information on can before use.**

Safety datasheet (SDS 534) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Weathershield, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.

### Cleaning Up

After use, remove as much product as possible from brushes before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp).

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/d): 130g/l (2010).

**Ready mixed:** This product contains max. 80g/l VOC. VOC content: Medium (8-24.99%).

**Tinted colour:** This product contains max. 90g/l VOC. VOC content: Medium (8-24.99%).



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)

**AkzoNobel**