

Nordsjö Perform+ Bathroom

April 2018



Product description

Nordsjö Perform+Bathroom is a satin waterborne wall paint intended for interior walls made of plaster, concrete, various types of boards (e.g. plywood, plaster, chip), fibreglass wallpapers for painting, etc. Nordsjö Perform+Bathroom can also be used for painting walls and ceiling that are cleaned/scrubbed frequently and need to be very durable.

It is primarily used for painting walls in bathrooms, catering facilities, food industry premises and similar environments, hospitals and other areas that are exposed to a lot of wear and tear.

Directions for use

Filler should be applied to plaster, concrete and other sheet materials wherever necessary using Nordsjö ProfessionalVåtrumspackel. Use Nordsjö Perform+Bathroom Primer for bonding and priming wallpaper in one step during the hanging process. Apply 2 coats of Nordsjö Perform+Bathroom using a new roller. Allow the painted walls to dry for 7 days before exposing them to water. Do not paint if the temperature in the room below +10 °C.

Other

Nordsjö Perform+Bathroom is part of the Nordsjö wet room system, approved in accordance with the Swedish industry standard (MVK) for wet rooms.

Health and environment

When sanded or treated with a heat gun, coats of paint may give off dust and/or vapour that is hazardous to health. Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove paint from all tools (brushes, rollers, etc.) before cleaning. Immediately clean all tools after painting. Do not flush liquid paint residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.



Technical data

Typical use: Interior
Binder: Acrylic copolymer dispersion
Gloss: Halvblank 30 (satin)
Drying time 23°C 50% RH: Fully dry after 2 hours, Recoat after 5 hours
Application temp: Min. +5°C
Humidity RH: 40-80% RF (65% RF is optimal)
Thinning: Water
Tools: Brush, roller, spray
Paint consumption: 6-8 m²/litre
Package sizes: 1L, 2.5L, and 10L
Bases: BW, BM
Cleaning: Soapy water
Storage: Frost-free
EU VOC limit value (Cat. A/b) 100g/l
Contains Max 2g/l

This declaration applies to the colour white.
The figures may vary for other colours.

AkzoNobel

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website.
AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009