

Nordsjö Professional Grov Rullspackel (Filler)

March 2019



Product description

Nordsjö Professional Grov Rullspackel is a very high coverage filler, applied with a roller indoors, that has been specially designed for use in repair and maintenance work, as well as new construction. Nordsjö Professional Grov Rullspackel is particularly suitable for surfaces where there are very high requirements on coverage. Nordsjö Professional Grov Rullspackel is a good choice for use on walls that are being repainted (washed and sanded first) and for painting over wallpaper and textured wallpaper. Nordsjö Professional Grov Rullspackel is suitable for filling holes and cracks, as well as resurfacing plaster, concrete, lightweight concrete and drywall in dry, interior spaces.

For resurfacing, it is recommended that a maximum thickness of 3 mm is applied. For filling individual holes and unevenness, up to 10 mm thickness is suitable.

Directions for use

Only apply to solid, clean and dry surfaces. Nordsjö Professional Grov Rullspackel is applied using a roller and in thick layers, after which a fine layer is applied using a filler with a finer grain. Make sure that the filler has dried completely before resurfacing or painting. When sanding, it is recommended that you wear eye protection and a dust mask.

Do not apply filler when the temperature in the room is below +5 °C.

Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.

Technical data

Typical use: Interior
Binder: Copolymer latex
Particle size: Max 0.40 mm
Density: 0.90
Drying time 23°C 50% RF: 4 hours, depending on the thickness
Application temp: Min +5°
Humidity RH: 40-80% RF (65% RF is optimal)
Thinning: Water
Tools: Roller
Package sizes: 15L
Sandability: May be lightly sanded
Colour: Grey tint
Storage: Frost-free

Meets the requirements for CE marking in accordance with EU Directive: EN 15824

Environment

This product meets the requirements for the Nordic Swan Ecolabel.

For more information: www.nordic-ecolabel.org

AkzoNobel

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00