

# Nordsjö Professional Grund +

February 2019



## Product description

Nordsjö Professional Grund + is a dead mat (fully matte), water based primer that is intended for painting interior walls and ceilings.

It has a high dry matter content, offers good coverage and provides excellent adhesion when applied to various types of substrates. After applying the final coats of paint, the unique composition of the product gives a final result that is incredibly even in its gloss and structure.

Nordsjö Professional Grund + is suitable for use on plaster, concrete, lightweight concrete, various types of boards (e.g. plywood, plaster, chip), fibreglass wallpapers for painting, etc.

## Directions for use

Filler should be applied to plaster, concrete and other sheet materials wherever necessary.

Nordsjö Professional Binder should be applied before painting whitewashed walls or surfaces that have poor binding qualities. Walls that are being repainted should first be washed using Original Målarvätt (cleaner).

If your original surface is shiny, you'll need to lightly sand it down using a fine grade of sandpaper. Use Grund + primer first.

For best results, apply 1 coat Grund + (primer) plus 1-2 coats of the selected paint for final coating.

Do not paint if the temperature in the room below +5 °C.

## Health and environment

When sanded or treated with a heat gun, coats of paint may give off dust and/or vapour that is hazardous to health.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove paint from all tools (brushes, rollers, etc.) before cleaning. Immediately clean all tools after painting. Do not flush liquid paint residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre.

Packaging should be submitted for recycling.

## Technical data

**Typical use:** Interior

**Binder:** Copolymer dispersion

**Drying time 23°C 50% RH:** Touch dry after 1 hour, Recoat after 2 hours

**Application temp:** Min. +5°C

**Humidity RH:** 40-80% RH (65% RH is optimal)

**Thinning:** Water

**Tools:** Brush, roller, spray

**Paint consumption:** 5-8 m<sup>2</sup>/litre

**Package sizes:** 2.5L, 10L and 100L

**Bases:** BW

**Cleaning:** Soapy water:

**Storage:** Frost-free

**EU VOC limit value (Cat. A/a)** 30g/l

Contains Max 1g/l

This declaration applies to the colour white. The figures may vary for other colours.

Classified as a flammable liquid. Meets the requirements for fire rating B-s1, d0, as per EU type approval 2439/79 and SC0710-15

## Environment

This product meets the requirements for the EU Ecolabel and the Nordic Swan Ecolabel

-Minimise the amount of leftover paint by estimating in advance the amount that you will need.

-Properly seal and store any leftover paint so that you will be able to use it again.

-When you use leftover paint, you help lower the product's environmental impact throughout its entire life cycle.

For more information: [www.nordic-ecolabel.org](http://www.nordic-ecolabel.org)

**AkzoNobel**

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

*The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website.*

*AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009*