Nordsjö Professional Multisprutspackel (Spray filler) January 2018





Nordsjö Professional Multisprutspackel is a white, universal lightweight filler for spray application and grouting indoors in dry areas. The composition of Nordsjö Professional Multisprutspackel also makes it suitable for affixing drywall tape in accordance with the requirements stated in HusAMA 14.

Nordsjö Professional Multisprutspackelspeciellt is a filler for spray application that has been specially designed for use in repair and maintenance work, as well as new construction. It is suitable for filling holes and cracks, as well as resurfacing plaster, concrete, lightweight concrete and drywall, along with filling/resurfacing on prior painted surfaces (washed and sanded down).

Directions for use

Only apply to solid, clean and dry surfaces. Suitable sprayers include: Wagner HC 960/970, El-Mygga, Graco Mark VII/ Mark X, APX8200, JETPRO 80-120.

When sanding, it is recommended that you wear eye protection and a dust mask.

Store in a frost-free place.

Do not apply filler when the temperature in room is below +5 °C.

Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet.

Firmly reseal any opened sacks. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.



 ϵ

Technical data

Typical use: Interior Binder: Copolymer latex Particle size: Max 0.15 mm

Density: 1.15

Drying time 23°C 50% RH: 4 hours,

depending on the thickness **Filling depth:** approx. 3 mm **Application temp:** Min. +5°C

Humidity RH: 40-80% RF (65% RF is optimal)

Thinning: Water
Tools: Putty knife
Colour: White
Package sizes: 14L
Cleaning: Soapy water:
Storage: Frost-free

Meets the requirements for CE marking in accordance with EU Directive: EN 13963 &

EN 15824

AkzoNobel