

Nordsjö Professional P10

September 2019



Product description

Nordsjö Professional P10 is a waterborne, durable, matte acrylic wall paint intended for interior walls made of plaster, concrete, lightweight concrete, various types of boards (e.g. plywood, plaster, chip), fibreglass wallpapers for painting, etc.

Directions for use

Filler should be applied to plaster, concrete and other sheet materials wherever necessary.

For best results, Nordsjö Professional Microdispers should be applied first, as a primer, on untreated plaster, concrete, drywall, cement fibreboard, bricks and resurfaced walls.

Finish with 2 coats of Nordsjö Professional P10.

It is also possible, on the surfaces mentioned above, to prime using Nordsjö Professional Grund + and then apply 1-2 coats of Nordsjö Professional P10.

Walls that are being repainted should first be washed using Original Målartvätt (cleaner).

If your original surface is shiny, you'll need to lightly sand it down using a fine grade of sandpaper. Apply 1-2 coats of Nordsjö Professional P10.

Nordsjö Professional Binder should be applied before painting whitewashed walls or surfaces that have poor binding qualities.

Do not paint if the temperature in the room below +5 °C.

Health and environment

When sanded or treated with a heat gun, coats of paint may give off dust and/or vapour that is hazardous to health.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove paint from all tools (brushes, rollers, etc.) before cleaning. Immediately clean all tools after painting. Do not flush liquid paint residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre.

Packaging should be submitted for recycling.

Technical data

Typical use: Interior

Binder: Acrylic copolymer dispersion

Gloss: Matt 10 (matte)

Drying time 23°C 50% RH: Touch dry after 2 hours, Recoat after 6 hours

Application temp: Min. +5°C

Humidity RH: 40-80% RF (65% RF is optimal)

Thinning: Water

Tools: Brush, roller, spray

Paint consumption: 6-8 m²/litre

Package sizes: 2.5L and 10L

Bases: BW, BM, BC, S0502-Y and S0500-N

Cleaning: Soapy water:

Storage: Frost-free

EU VOC limit value (Cat. A/a) 30g/l

Contains Max 1g/l

This declaration applies to the colour white. The figures may vary for other colours.

Classified as a flammable liquid. Meets the requirements for fire rating B-s1, d0, as per EU type approval SC0710-15
Wet scrub resistance according to Class 1 of EN 13300

Environment

This product meets the requirements for the Nordic Swan Ecolabel.

-Minimise the amount of leftover paint by estimating in advance the amount that you will need.

-Properly seal and store any leftover paint so that you will be able to use it again.

-When you use leftover paint, you help lower the product's environmental impact throughout its entire life cycle.

For more information: www.svanen.se

AkzoNobel

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website. AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009