

# Nordsjö Professional P25

September 2019



## Product description

Nordsjö Professional P25 is a waterborne, semi-matte, durable acrylic wall paint that offers excellent coverage for creating a modern surface in rooms that get plenty of light. Nordsjö Professional P25 is intended for interior walls made of plaster, concrete, lightweight concrete, various types of boards (e.g. plywood, plaster, chip), fibreglass wallpapers for painting, etc. It is primarily used for painting walls in kitchens, hallways, common areas, offices rooms, classrooms, hospitals and in industrial settings where a semi-gloss surface is desired that can be washed.

## Directions for use

Filler should be applied to plaster, concrete and other sheet materials wherever necessary. For best results, Nordsjö Professional Microdispers should be applied first, as a primer, on untreated plaster, concrete, drywall, cement fibreboard and resurfaced walls. Finish with 2 coats of Nordsjö Professional P25. It is also possible, on the surfaces mentioned above, to prime using Nordsjö Professional Grund + and then apply 1-2 coats of Nordsjö Professional P25.

Walls that are being repainted should first be washed using Nordsjö Original Målarvätt (cleaner).

If your original surface is shiny, you'll need to lightly sand it down using a fine grade of sandpaper. Apply 1-2 coats of Nordsjö Professional P25. Nordsjö Professional Binder should be applied before painting whitewashed walls or surfaces that have poor binding qualities.

Do not paint if the temperature in the room below +5 °C.

## Health and environment

When sanded or treated with a heat gun, coats of paint may give off dust and/or vapour that is hazardous to health.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove paint from all tools (brushes, rollers, etc.) before cleaning. Immediately clean all tools after painting. Do not flush liquid paint residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.

## Technical data

**Typical use:** Interior

**Binder:** Acrylic copolymer dispersion

**Gloss:** Halvmatt 25 (semi-matte)

**Drying time 23°C 50% RH:** Touch dry after 2 hours, Recoat after 6 hours

**Application temp:** Min. +5°C

**Humidity RH:** 40-80% RF (65% RF is optimal)

**Thinning:** Water

**Tools:** Brush, roller, spray

**Paint consumption:** 6-8 m<sup>2</sup>/litre

**Package sizes:** 2.5 L, 5L and 10L

**Bases:** BW, BM, BC and S0500-N

**Cleaning:** Soapy water:

**Storage:** Frost-free

**EU VOC limit value** (Cat. A/b) 100g/l

Contains Max 31g/l

This declaration applies to the colour white.

The figures may vary for other colours.

Classified as a flammable liquid. Meets the requirements for fire rating B-s1, d0, as per EU type approval SC0710-15

Wet scrub resistance according to Class 1 of EN 13300

*The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website. AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009*