

# Nordsjö Professional Rullspackel (Roller filler)

March 2019



## Product description

Nordsjö Professional Rullspackel is a universal, high coverage filler applied with a roller indoors, that has been specially designed for use in repair and maintenance work, as well as new construction. It is suitable for filling holes and cracks, as well as resurfacing plaster, concrete, lightweight concrete and drywall, wallpaper seams, painted interior surfaces in dry areas, etc.

The composition of Nordsjö Professional Rullspackel also makes it suitable for affixing drywall tape in accordance with the requirements stated in HusAMA 18.

For resurfacing, it is recommended that a maximum thickness of 3 mm is applied. For filling individual holes and unevenness, up to 5 mm thickness is suitable.

## Directions for use

Only apply to solid, clean and dry surfaces. Suitable for use with long-handled roller. For the best final results, use a wide spatula to smooth walls/ceilings. When sanding, it is recommended that you wear eye protection and a dust mask.

Do not apply filler when the temperature in room is below +5 °C.

## Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet.

Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.

## Technical data

**Typical use:** Interior

**Binder:** Copolymer latex

**Particle size:** Max 0.16 mm

**Density:** 1.0

**Drying time 23°C 50% RH:** 4 hours, depending on the thickness

**Application temp:** Min. +5°C

**Humidity RH:** 40-80% RF (65% RF is optimal)

**Thinning:** Water

**Tools:** Putty knife

**Sandability:** May be lightly sanded

**Colour:** Grey tint

**Package sizes:** 15L

**Cleaning:** Soapy water:

**Storage:** Frost-free

Meets the requirements for CE marking in accordance with EU Directive: EN 13963 & EN 15824

## Environment

This product meets the requirements for the Nordic Swan Ecolabel.

For more information: [www.nordic-ecolabel.org](http://www.nordic-ecolabel.org)

**AkzoNobel**

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website. AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009