

# Nordsjö Professional Våtrumsspackel (Wet room filler)

March 2019



## Product description

Nordsjö Professional Våtrumsspackel is a high coverage filler suitable for filling holes and cracks, as well as resurfacing, concrete, lightweight concrete and drywall and for affixing drywall tape.

Nordsjö Professional Våtrumsspackel is primarily used in wet rooms or areas where a water-resistant filler is needed.

Nordsjö Professional Våtrumsspackel is part of the Nordsjö wet room system, approved in accordance with the Swedish industry standard (MVK) for wet rooms (see separate brochure). The product meets the requirements stated in HusAMA 18 for filler in wet rooms.

For resurfacing, it is recommended that a maximum thickness of 3 mm is applied. For filling individual holes and unevenness, up to 5 mm thickness is suitable.

## Directions for use

Only apply to solid, clean and dry surfaces. Nordsjö Professional Våtrum is intended for filler jobs done by hand. When sanding, it is recommended that you wear eye protection and a dust mask.

Store in a frost-free place.

Do not apply filler at temperatures below +5 °C.

## Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet.

Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain.

Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.

### Technical data

**Typical use:** Interior

**Binder:** Copolymer latex

**Particle size:** Max 0.16 mm

**Density:** 1.10

**Drying time 23°C 50% RH:** 4 hours, depending on the thickness

**Wet abrasion resistance (method-modified SS184164):** More than 2,000 abrasion cycles

**Application temp:** Min. +5°C

**Humidity RH:** 40-80% RH (65% RH is optimal)

**Thinning:** Water

**Tools:** Filler done by hand. With a machine, after dilution of approximately 3%.

**Sandability:** May be lightly sanded

**Colour:** Blue tint

**Package sizes:** 250 g, 2.5L and 10L

**Cleaning:** Soapy water:

**Storage:** Frost-free

Meets the requirements for CE marking in accordance with EU Directive: EN 13963 & EN 15824

**AkzoNobel**

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website.  
AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009