

SADOLIN DULUX STUCCO PUTTY EXTERIOR



Product Name	Sadolin Dulux Stucco Putty Exterior	
Description and Usage	<p>Sadolin Dulux Stucco Putty Exterior can fill minor cracks and even the surface for a smooth exterior finish.</p> <p>Sadolin Dulux Stucco Putty Exterior is suitable on exterior surfaces for filling of minor dents and surface irregularities on substrates such as plaster, concrete building boards, plywood etc. Should be applied on primed or previously painted surfaces after necessary preparation.</p>	
Benefits	<ul style="list-style-type: none"> • High solids • Excellent filling • Easy to apply • No sinking or cracking 	
Pack Size	4 Litre and 18 Litre	
Colour Range	Off White	
Film Properties		
<i>Water Resistance</i>	Will tolerate a slightly damp surface but is not suitable where the surface is saturated.	
Composition (nominal)	Pigment	: Non-lead Pigments
	Binder	: Styrene-Acrylic Emulsion
	Solvent	: Water
Volume Solids	Fine: 60% ± 2 , Coarse: 72% ± 2	
Drying Times	Single coat at standard thickness:	
<i>Touch Dry</i>	Dependent on temperature and humidity	
<i>Recoat</i>	6 - 8 hours	
Film Thickness	100 microns dry film thickness	
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 1.5 – 3.5 m ² /litre/coat.	
Application	Trowel or Putty Knife	
Thinning	Up to 3 % clean water if required to achieve application consistency.	

SADOLIN DULUX STUCCO PUTTY EXTERIOR



Cleaning Up	Clean all equipment with water immediately after use.			
Surface Preparation	Sadolin Dulux Stucco Putty Exterior should be applied only on primed surfaces in new painting or previous painted surface. Sand the surface after it has completely dried and remove all loose powder. Overcoat the putty with a suitable primer.			
System Information	Sealer (1 coat)	Putty (1 coat)	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Sadolin Dulux Exterior Primer SB	Sadolin Dulux Stucco Putty Exterior	Sadolin Dulux Weathershield Primer	Sadolin Dulux Weathershield range of products
<i>New, Normal, Sound Surfaces</i>	Sadolin Dulux Weathershield Primer			

Health, Safety and Environment Information

Product Safety Data Sheet available upon request.

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Oman SAOC

P.O. Box 531, Ruwi, Postal code 112
 Sultanate of Oman
 Tel: (968) 24446218 Fax: (968) 24446962
 Email: sadolin.dulux@akzonobel.com
 Website: www.sadolindulux.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.