

SADOLIN DULUX STUCCO PUTTY INTERIOR



Product Name	Sadolin Dulux Stucco Putty Interior						
Description and Usage	<p>Sadolin Dulux Stucco Putty Interior is an acrylic based quick drying putty with good filling properties. Sadolin Dulux Stucco Putty Interior imparts a very smooth finish.</p> <p>Sadolin Dulux Stucco Putty Interior is suitable for filling of minor dents and surface irregularities on substrates such as plaster, concrete building boards, plywood etc. Should be applied on primed or previously painted surfaces after necessary preparation.</p>						
Benefits	<ul style="list-style-type: none"> • Easy to apply by trowel and putty blade • Good filling • No shrinking or cracking 						
Pack Size	4 Litre and 18 Litre						
Colour Range	White						
Film Properties							
<i>Water Resistance</i>	Will tolerate a slightly damp surface but is not suitable where the surface is saturated.						
Composition (nominal)	<table> <tr> <td>Pigment</td> <td>: Non-lead Pigments</td> </tr> <tr> <td>Binder</td> <td>: Styrene-Acrylic Emulsion</td> </tr> <tr> <td>Solvent</td> <td>: Water</td> </tr> </table>	Pigment	: Non-lead Pigments	Binder	: Styrene-Acrylic Emulsion	Solvent	: Water
Pigment	: Non-lead Pigments						
Binder	: Styrene-Acrylic Emulsion						
Solvent	: Water						
Volume Solids	45%						
Drying Times	Single coat at standard thickness:						
<i>Touch Dry</i>	Dependent on temperature and humidity						
<i>Recoat</i>	8 - 10 hours						
Film Thickness	100 microns dry film thickness						
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 4.0 – 6.0 m ² /litre/coat.						
Application	Trowel or Putty Knife						
Thinning	Up to 3 % clean water if required to achieve application consistency.						

SADOLIN DULUX STUCCO PUTTY INTERIOR



Cleaning Up	Clean all equipment with clean water immediately after use.			
Surface Preparation	Sadolin Dulux Stucco Putty Interior should be applied only on primed surfaces in new painting or previous painted surface. Sand the surface after it has completely dried and remove all loose powder. Overcoat the putty with a suitable primer.			
System Information	Sealer (1 coat)	Putty (1coat)	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Sadolin Dulux Interior Primer SB	Sadolin Dulux Stucco Putty Interior	Sadolin Dulux Interior Super Primer WB	Sadolin Dulux Interior range of products
<i>New, Normal, Sound Surfaces</i>	Sadolin Dulux Interior Super Primer WB			
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.			

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Oman SAOC
P.O. Box 531, Ruwi, Postal code 112
Sultanate of Oman
Tel: (968) 24446218 Fax: (968) 24446962
Email: sadolin.dulux@akzonobel.com
Website: www.sadolindulux.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.