

NEOPAL Easycare Eco

Easy to clean paint



Ecological emulsion paint

DESCRIPTION

NEOPAL Easycare Eco is an ecological emulsion paint which thanks to its innovative formula it repels water-soluble stains, preventing them from entering deeper in the coat. It is proven to be much more resistant to wet scrubbing compared with common emulsion paint. It has excellent working and levelling properties, superior whiteness, great coverage and gives a luxurious velvet finish. Eco certified according to the new criteria of the European Union Eco-labeling Board (EUEB). It is recommended for surfaces levelled with putty, hardboard, plaster, concrete. It creates a protective film with the highest resistance to water-soluble stains, such as juice, tea, soft drinks, mud, chocolate, ketchup, making the cleaning process a piece of cake.

PRODUCT INFORMATION

Application method: Brush, roller or airless spray.

Thinning: 5-10% clean water.

Spreading rates: About 12m² per litre per coat on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 3 hours. Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in white and in unlimited number of shades through Vivechrom's tinting system CHROMOSYNTHESIS.

Storage: Store between 5° to 40° C.

Stain-repellent technology

Much more resistant to wet scrubbing

STAIN REMOVAL

Full properties of wet scrub resistance are achieved after 20 days of completing the painting. The stains can be removed with a soft sponge and soapy water and no longer than 15 minutes after the stain was created.

VOC (Volatile Organic Compounds)

EU limit value for this product category

A/a Interior matt walls and ceilings

(gloss ≤25@60°): 30 g/l (2010). This product contains max 10 g/l VOC.



FR 044/054



www.vivechrom.gr



NEOPAL® Easycare Eco

Easy to clean paint

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- Dry sanding will give rise to dust. Wet sanding/flatting should be used wherever possible.
- Ensure good ventilation during application and drying. Use suitable respiratory protective equipment.
- To fill and coat the surfaces: Use Vivechrom's STOKOS SPATOULARISMATOS or NEOPAL STUCCO.
- For new surfaces or porous surfaces coated with lime or low quality paints: Prime with NEOPAL PRIMER.
- For the refinishing of sound surfaces apply directly NEOPAL Easycare Eco. For the refinishing of sound surfaces apply directly NEOPAL Easycare Eco.

APPLICATION

- For best results use roller with thin nap
- Thin with 5-10% clean water and stir well before use.
- Apply 2 coats of NEOPAL Easycare Eco for a perfect result.
- Prior to applying dynamic shades that do not exhibit high opacity, apply one coat of NEOPAL Easycare Eco in a similar shade produced by the highest opacity Base.
- Ensure good ventilation during application and drying.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.
- Minimise paint wastage by estimating how much paint you will need"
- Ensure good ventilation during application and drying.

AFTER USE – WASTE MANAGEMENT

- Remove as much paint as possible from brushes and rollers before cleaning
- Clean brushes and equipment with water and detergent solution after use
- Do not put residual paint down the kitchen sink or toilet, or into a waste bin
- Unused paint requires specialist handling for safe environmental disposal and that it should not therefore be thrown away with household refuse
- Advice regarding disposal and collection should be sought from the local authority
- Recover unused paint for re-use
- Reuse of paint can effectively minimise the products' life cycle environmental impact.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand

- Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction • Close well after application • Store in a cool place • Lift with care – gross weight exceeds 10 kg.

Emergency Tel. Number of Official Advisory Body: +30210 7793777

For more information as to why this product has been awarded the Flower please visit the web-site: <http://www.ecolabel.eu>.

STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.



www.vivechrom.gr