

CHASSICOAT

Antirust Enamel paint for chassis



DESCRIPTION

CHASSICOAT is a quick drying solvent-based paint for the protection of chassis of vehicles. It is also suitable as undercoat for any metallic surface. It has excellent coverage, strong adhesion and high elasticity. It exhibits strong resistance to chipping, humidity and petrol.

PRODUCT INFORMATION

Type: Alkyd based enamel paint.

Specific gravity: 1,14 - 1,28 gr/cm³ (ISO 2811) depending on the shade.

Viscosity: 5-6 ps (ROTOTHINNER DIN 51550, 25°C)

Application method: Brush, roller or spray gun.

Thinning: Up to 10% v/v with VIVECHROM's BRUSH SOLVENT for use with brush/roller, up to 20% v/v with VIVECHROM's SPRAY GUN SOLVENT for use with spray gun.

Spreading rates: About 13 m² per litre on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 16 hours. Drying time depends on weather conditions (humidity, temperature).

Colours: It is available in black and brown.

Storage: Store between 5° to 40° C.

Strong adhesion and high elasticity

Strong resistance

VOC (Volatile Organic Compounds)

EU limit value for this product category A/i one-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC.





CHASSICOAT

Antirust Enamel paint for chassis

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt and grease and bethoroughly rubbed down using a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

APPLICATION

- Thin up to 10% v/v BRUSH SOLVENT for use with brush/roller and up to 15% v/v with SPRAY GUN SOLVENT for use with spray gun.
- Apply one or two coats of CHASSICOAT. Sanding between coats is recommended using a suitable abrasive paper.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT by Vivechrom.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Xylene- Naphtha (petroleum), hydrotreated heavy • Flammable liquid and vapour • Causes skin irritation • Harmful to aquatic life with long lasting effects • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Avoid release to the environment • Repeated exposure may cause skin dryness or cracking • Dispose of contents and container in accordance with all national regulations • Contains 2-butanone oxime. May produce an allergic reaction.
Poison Center: +30210 7793777



**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



