

# SFIRILATO

Protective & decorative enamel paint  
with hammered effect finish



## DESCRIPTION

**SFIRILATO** is a protective and decorative enamel paint that provides an attractive hammered metal decorative appearance. **SFIRILATO** is the easy and effective solution for decoration and protection of metallic surfaces, such as elevator doors, railings, metallic furnitures, handrails, decorative small objects e.t.c. It is quick drying with strong adhesion.

## PRODUCT INFORMATION

**Type:** Enamel paint based on special synthetic resins.

**Specific gravity:** 0,94 – 0,98±0,01 gr/cm<sup>3</sup> (ISO 2811)

**Viscosity:** 70-100 sec (FC4/ASTM D1200)

**Application method:** Spray gun, roller, brush.

**Thinning:** Up to 18% v/v with VIVECHROM's THINNER N600 GENERAL USE

**Spreading rates:** About 8m<sup>2</sup> per litre on previously prepared surfaces

**Drying times:** Touch dry in 20 min. Drying time depends on weather conditions (humidity, temperature)

**Colours:** It is available in 16 shades from factory colourcard

**Storage:** Store between 5° to 40° C. If you do not use the whole quantity, close carefully the lid for next use.

High strength and gloss

Quick drying

### VOC (Volatile Organic Compounds)

EU limit value for this product category

A/i one-pack performance coatings: 500g/l (2010).

This product contains max 499g/l.





## SFIRILATO

**Protective & decorative enamel paint  
with hammered effect finish**

### SURFACE PREPARATION

- Surfaces must be clean and dry.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

### APPLICATION

- In order to achieve the hammer effect finish, apply one thick coat of SFIRILATO thinned up to 18% with THINNER No 600 GENERAL USE by Vivechrom. For small surfaces and application with brush or roller, apply 1-2 coats without thinning.
- For exterior use, apply initially necessarily the primer RUST PRIMER for antirust protection.
- Ensure that the surface is adequately covered and there are no pinholes to allow moisture penetration.

### AFTER USE

Remove as much paint as possible from equipment before cleaning • Clean equipment with THINNER No 600 GENERAL USE by Vivechrom after use.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

**DANGER.** Contains xylene and butanone • Highly flammable liquid and vapour • Causes skin irritation • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Repeated exposure may cause skin dryness or cracking • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Contains 2-butanone oxime • May produce an allergic reaction.

Poison Tel Center: 210 7793777.



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



[www.vivechrom.gr](http://www.vivechrom.gr)