

VIVELOCK METALLIZED

Enamel Paint Direct to Rust



DESCRIPTION

VIVELOCK METALLIZED is a protective and decorative paint, which gives an excellent rough mat metallized finish to the coated surface. It is applied directly on corroded metallic surfaces, with no need for anticorrosive primer. It also exhibits good adhesion on galvanized surfaces. VIVELOCK METALLIZED is the easy and effective solution for decoration, protection and renewal of interior and exterior metallic surfaces, for the house and all the contemporary buildings, such as doors, railings, columns, handrails and small metalwork items. It provides excellent antirust protection with long term colour retention. It exhibits strong adhesion, very good working and leveling properties and gives a spectacular result.

Strong Adhesion

PRODUCT INFORMATION

Type: Enamel paint based on specially modified alkyd resins.

Specific gravity: 1,49 - 1,52 gr/cm³(ISO 2811), depending on shade

Viscosity: 11,5 - 12,5 P (ROTOTHINNER DIN 51550, 25 OC)

Application method: Brush or spray gun

Thinning: Use with brush : Ready for use. If thinning is necessary, add up to 3% v/v VIVECHROM's BRUSH SOLVENT

Use with spray gun: Up to 25% v/v with VIVECHROM's SPRAY GUN SOLVENT

Spreading rates: About 3,5 - 7 m² per litre on previously prepared surfaces, for 150 - 75 µm dry film thickness respectively

Drying times: Touch dry after 4 hours and can be recoating the next day (24 hours). Drying time depends on weather conditions (humidity, temperature)

Colours: Available in 6 readymade colours

VOC (Volatile Organic Compounds)

EU limit value for this product (category A/i) one-pack performance coatings: 500g/l (2010). This product contains max 499g/l.

Impressive metallized finish





VIVELOCK METALLIZED

Enamel Paint Direct to Rust

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt and grease and be thoroughly rubbed down using a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

APPLICATION

- Application with brush: Ready for use. Apply two thick coats of VIVELOCK METALLIZED.
- Application with spray gun: Apply three coats of VIVELOCK METALLIZED thinned up to 25% with Gun Solvent.
- For perfect finish in large surfaces prefer application with spray gun. Ensure that all corners and difficult points are adequately covered, and that there are no pinholes which allow moisture to penetrate.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT by Vivechrom.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains- Naphtha (petroleum), hydrotreated heavy.

- Flammable liquid and vapour • Keep out of reach of children • If medical advice is needed, have product container or label at hand.
- Keep away from heat, sparks, open flames and hot surfaces • No smoking • Keep container tightly closed • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell
- Keep cool • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Repeated exposure may cause skin dryness or cracking • Contains 2-Butanone oxime. May produce an allergic reaction.

Poison Tel Center: 210 7793777.



**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr