

# AQUAXYL® VARNISH

## Water Based Woodstain



### DESCRIPTION

**AQUAXYL VARNISH** is a water based woodstain, both for interior and exterior use. It gives a beautiful gloss or satin finish that enhances the beauty of the natural wood. It is applicable on doors, windows, frames, claddings and any wooden surface. It is odourless and it is applied easily. It is highly flexible and it does not crack, blister or peel. It contains UV filters for effective protection from the sun's ultraviolet rays. It is water repellent and allows the wood to breathe.

**Odourless**

**Flexible and resistant**

**UV filter: sun protection**

### PRODUCT INFORMATION

**Type:** Water based woodstain, based on synthetic resins.

**Application method:** Brush, roller or spray gun.

**Thinning:** 5-10% (brush, roller), 20-25% (spray gun) with clean water

**Spreading rates:** About 9-12 m<sup>2</sup> per litre per coat on previously prepared surfaces.


**Drying times:** Touch dry after 1 hour and recoatable after 6 hours. Drying time depends on weather conditions (humidity, temperatures).

**Colours:** It is available in colourless in gloss and satin finish, in 12 ready-made satin shades, as well as in 34 satin and gloss shades through VIVECHROM's tinting system CHROMOSYNTHESIS.

**Storage:** Store between 5° to 40° C.

#### VOC (Volatile Organic Compounds)

EU limit value for this product category A/e  
Interior/exterior trim varnishes and woodstains, including opaque woodstains: 130g/l (2010). This product contains max 80 g/l VOC.



[www.vivechrom.gr](http://www.vivechrom.gr)



## AQUAXYL® VARNISH

### Water Based Woodstain

#### SURFACE PREPARATION

- Surfaces must be clean and dry and rubbed down with a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

#### APPLICATION

- Thin with 5-10% (brush, roller), 20-25% (spray gun) with clean water and stir well before use.
- Apply 1-2 coats of **AQUAXYL VARNISH**. For maximum durability and up to 5 years protection, high quality of the wood and the construction is required and application of minimum 3 coats of coloured **AQUAXYL VARNISH**.
- When the Colourless 701 is applied, it is lightly milky, but as it dries it creates a totally transparent film.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

#### AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

#### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: 1,2-benzisothiazol-3(2H)-one, CIT/MIT(3:1) and OIT. May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Poison Control Center for Greece: +30210 7793777 / for Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



[www.vivechrom.gr](http://www.vivechrom.gr)