

ASTARI GYPSOSANIDON ECO

ECOLOGICAL GYPSUM BOARD PRIMER



DESCRIPTION

Vivechrom's ASTARI GYPSOSANIDON ECO is a high quality ecological acrylic waterborne primer for interior use, suitable for gypsum boards and other absorbent surfaces such as plaster, surfaces leveled with stucco and more. Due to its excellent filling properties, it smooths imperfections and surface irregularities of the gypsum board. Moreover, it perfectly balances the absorbency between the leveled with stucco surfaces and the gypsum board, ensuring a flawless end result, after painting it with emulsion paint. It has high whiteness, excellent coverage and strong adhesion. It has very good application properties, levelling and spreading rate and it dries fast.

Excellent Filling properties and high hiding power

Smoothing of imperfections and irregularities

Balancing of substrate absorbency differences

PRODUCT INFORMATION

Type: Ecological Acrylic waterborne gypsum board primer

Specific gravity: (ISO2811) 1,68 ± 0,02 gr/ml

Viscosity: 12-16 P (RT DIN 51550), 25°C

Application Method: Roller, brush or airless spray

Thinning: Up to 5-10% with clean water.

Spreading Rates: About 12 m²/lt per coat depending on thinning and the absorbency of the surface.

Drying timers: Touch dry in 1 hour. Recoatable, if needed, after 3 hours. Drying time depends on weather conditions (humidity, temperature etc)

Storage: Store between 5°C and 40°C.

VOC (Volatile Organic Compounds)

EU Limit Values for this product category

A/g Primers WB: 30 g/l (2010).

This product contains max 10 g/l VOC.





ASTARI GYPSOSANIDON ECO

ECOLOGICAL GYPSUM BOARD PRIMER

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering materials, dirt, grease and salts.
- Treatments such as sanding may generate hazardous dust. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- To fill and coat the surfaces: Use VIVECHROM's STOKOS SPATOULARISMATOS.

APPLICATION

- Thin up to 5-10% with clean water and stir well before use.
- Apply one coat of ASTARI GYPSOSANIDON ECO
- Ensure good ventilation during application and drying.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.
- Minimize paint wastage by estimating how much paint you will need.

AFTER USE

- Remove as much paint as possible from brushes and rollers before cleaning.
- Clean brushes and equipment with water and detergent solution after use
- Do not empty into drains
- Do not put residual paint down the kitchen sink or toilet, or into a waste bin
- Unused paint requires specialist handling for safe environmental disposal and that it should not therefore be thrown away with or commercial waste. Advice regarding disposal and collection should be sought from the local authority
- Recover unused paint for re-use
- Reuse of paint can effectively minimize the products' life cycle environmental impact.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Poison Tel Center: 210 7793777 / for Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**

