

Fit™ ACRYLIC

Acrylic Paint for General Use in Exterior Surfaces



DESCRIPTION

FIT ACRYLIC is an acrylic paint for general use in exterior surfaces from plaster, concrete, bricks with good resistance to weather conditions and to high alkalinity. It represents the economic proposition by VIVECHROM, for surfaces where frequent painting and freshening up is needed such as schools, hotels, big public works. It has strong adhesion, good coverage and whiteness. It has very good working and leveling properties and dries fast creating nice matt surface.

Very Good Working and Leveling properties

Good Coverage

PRODUCT INFORMATION

Type: 100% Acrylic paint.

Specific gravity: 1,44 ± 0,02gr/cm³ (ISO 2811).

Viscosity: 10-13 ps (ROTOTHINNER DIN 51550, 25°C).

Application method: Brush, roller or airless spray.

Thinning: 5-10% clean water

Spreading rates: About 9 m² per litre per coat on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 3 hours. Drying time depends on weather conditions (humidity, temperature).

Colours: It is available in White. Also, it is available through VIVECHROM's tinting system CHROMOSYNTHESIS in unlimited number of shades.

Storage: Store between 5° to 40° C.

VOC (Volatile Organic Compounds)

EU limit value for this product category A/c
Paints for exterior walls of mineral substrate: 40g/l
(2010). This product contains max 8 g/l VOC.



www.vivechrom.gr

Vivechrom Dr STEFANOS D. PATERAS SA

FACTORY & HEAD OFFICES: THESI VATHI PIGADI, 19600 MANDRA ATTICA, GREECE TEL.:+30 210 5538700, FAX:+30 210 5550464
THESSALONIKI: ETHN. ANTISTASEOS 114, 55134 KALAMARIA, TEL.:+30 2310 450000, FAX:+30 2310 493984



Fit™ ACRYLIC

Acrylic Paint for General Use in Exterior Surfaces

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- For new surfaces or coated surfaces with chalking, prime with VIVE PRIMER 100% ACRYLIC PRIMER FOR EMULSION PAINTS.
- For sound surfaces, apply directly FIT ACRYLIC.

APPLICATION

- Thin with 5-10% clean water and stir well before use.
- Apply 2 coats of **FIT ACRYLIC** for a perfect result.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.


AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), and OIT. May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Poison Tel Center: 210 7793777 / for Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr