

SUPER NEOPAL®

Premium Quality Emulsion Paint



DESCRIPTION

SUPER NEOPAL is a premium quality emulsion paint, with great hiding power, superior whiteness and bright shades with long lasting colour stability. It is ammonia free and it is ideal for all interior areas. It is suitable for plaster, concrete, bricks, wood. It has great working and leveling properties, strong adhesion and quick drying. It gives a flawless matt finish, with outstanding resistance to frequent washing. It does not contribute to the growth of fire and it is flame retardant.

PRODUCT INFORMATION

Type: Emulsion paint based on PVA-VEOVA copolymer.

Specific gravity: 1,44 – 1,52 ± 0,02gr/cm³ (ISO 2811), depending on shade

Viscosity: 11-14ps (ROTOTHINNER DIN 51550, 25°C).

Application method: Brush, roller or airless spray.

Thinning: 5-10% clean water.

Spreading rates: About 12m² per litre per coat on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 3 hours.

Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in white and in 9 shades from factory colourcard. Also available in unlimited number of shades, through **Vivechrom's** tinting system **CHROMOSYNTHESIS**.

Storage: Store between 5° to 40° C. If you do not use the whole quantity, close carefully the lid for next use.

VOC (Volatile Organic Compounds)

EU limit value for this product category
A/a Paints for interior walls and ceilings
(gloss ≤25@60°): 30 g/l (2010). This product contains
max 11 g/l VOC.

High Coverage

Superior durability

Ammonia free



www.vivechrom.gr



SUPER NEOPAL®

Premium Quality Emulsion Paint

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- To fill and coat the surfaces: Use NEOPAL STUCCO.
- For new surfaces or porous surfaces coated with lime or low quality paints: Prime with NEOPAL PRIMER.
- For the refinishing of sound surfaces apply directly **SUPER NEOPAL**.

APPLICATION

- Thin with 5-10% clean water and stir well before use.
- Apply 2 coats of SUPER NEOPAL for a perfect result.
- Ensure good ventilation during application and drying.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

AFTER USE – WASTE MANAGEMENT

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and OIT. May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Poison Center for Greece: +30210 7793777 / For Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr