

TEAK OIL[®]

Maintains & Refreshes Hard Wood



DESCRIPTION

VIVECHROM'S TEAK OIL is a specially selected mixture of oils combined with wax, used mainly for maintaining and refreshing the hard wood such as teak, mahogany, iroko, as well as all the bare wood. It is absorbed into the wood saturating its pores without forming a film and it is water repellent. It revives and brings out the natural colour and texture of wood which has been worn out due to weather or use conditions. It is ideal for garden and interior unvarnished furniture as well as for wooden decorative objects.

PRODUCT INFORMATION

Type: Mixture of modified natural oils

Specific gravity: 0,84±0,02 gr/cm³ (ISO 2811)

Viscosity: 55-65 sec (DIN2, 25o C)

Application method: Cloth, brush

Thinning: Ready for use

Spreading rates: About 12m² per litre on softwood or 15m² per litre on hardwood

Drying times: Touch dry after 3 hours and recoatable after 2 days. Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in colourless

Storage: Store between 5°C to 40°C.

Revives and brings out the natural colour and texture

Water repellent



TEAK OIL[®]

Maintains & Refreshes
Hard Wood

SURFACE PREPARATION

- Surfaces must be clean and dry, unvarnished and free from dust, grease, and resin.
- Treatments such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.

APPLICATION

- Thin with up to 3% v/v with BRUSH SOLVENT and stir well before use.
- Apply 2 coats of VIVELUX in gloss or satin finish.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

AFTER USE – WASTE MANAGEMENT

Clean brushes and equipment with VIVECHROM's BRUSH SOLVENT immediately after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of the reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Repeated exposure may cause skin dryness or cracking • Do not empty into drains • Dispose of contents and container in accordance with all national regulations.

Contains 2-butanone oxime– May produce an allergic reaction.

Poison Center Tel. +302107793777 / for Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr