

# VIVEXYL® PLUS

Wood preservative



## DESCRIPTION

**VIVEXYL PLUS** is a coloured wood preservative solventbased for exterior use that penetrates into the wood and protects against fungi/ blue stains. It is applied to doors, windows, frames, claddings, garden furniture, rafters and beams, trellises. It is resistant to cracking, blistering and peeling. It has excellent durability to sunlight and moisture and offers effective protection enhancing the natural beauty of wood.

It is available in colourless and in 12 ready-made shades.

**Decoration & protection**

**High adhesion & durability**

## PRODUCT INFORMATION

**Type:** Wood preservative based on special synthetic resins. Fungicide to prevent fungal infection of the wood. Contains IPBC 0.7% w/w.

**Specific gravity:** 0.93±0,01 gr/cm<sup>3</sup> (ISO 2811)

**Viscosity:** 40-60sec (DIN 4, 53211 / 25o C)

**Application method:** Brush

**Thinning:** Ready for use

**Spreading rates:** About 14m<sup>2</sup> per litre per coat on softwood or 18m<sup>2</sup> per litre per coat on hardwood

**Drying times:** Touch dry after 3 hours and recoatable after 16 hours. Drying time depends on weather conditions (humidity, temperature)

**Colours:** It is available in colourless and in 12 ready shades.

**Storage:** Store between 5°C to 40°C.

### VOC (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product of category A/e Interior/exterior trim varnishes and woodstains, including opaque woodstains: 400g/l (2010). This product contains max 399g/l VOC.



[www.vivechrom.gr](http://www.vivechrom.gr)



# VIVEXYL® PLUS

## Wood preservative

### SURFACE PREPARATION

- Surfaces must be clean and dry and rubbed down with a suitable abrasive paper.
- Dust off new wood and remove grease and resin with THINNER No 600 for GENERAL USE.
- Treatments such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

### APPLICATION

- Ready for use. Apply 1-2 coats of VIVEXYL PLUS.
- For effective biocidal performance apply 200–250 ml/m<sup>2</sup>.
- Touch dry after 3 h and recoatable after 16 h.
- For a perfect satin finish, it is recommended to use VIVEXYL FILTER 7 premium woodstain as topcoat.
- This product is for use in all outside wood, which is not in direct contact to soil or surface water and it is exposed to weather conditions. Not for indoor use.
- The final colour of the wood depends on the physical colour and absorption of wood and the number of VIVEXYL PLUS coats applied.

### AFTER USE – WASTE MANAGEMENT

- Clean brushes and equipment with Vivechrom's BRUSH SOLVENT immediately after use • Do not empty into drains.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Harmful to aquatic life with long lasting effects • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or a doctor if you feel unwell • After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap • After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur • If swallowed: Do not induce vomiting unless expressly instructed by medical personnel • After inhalation: Move affected person into fresh air. Seek medical advice if symptoms are severe or long lasting • Avoid release to the environment • Dispose of contents to local rules. Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. Wear suitable protective clothing and gloves. Use biocides safely. Always read the label and product information before use.

Poison Center Tel.: +30210 7793777 / for Cyprus: 1401

Authorization Number for Greece: ΤΠ8-0117-ΟΠ / Authorization Number for Cyprus: KY-0078-1

Production Date: see bottom of container.

To be used within 3 years from production date.

**KEEP OUT OF REACH OF CHILDREN**



[www.vivechrom.gr](http://www.vivechrom.gr)

Vivechrom Dr STEFANOS D. PATERAS SA  
FACTORY & HEAD OFFICES: THESI VATHI PIGADI, 19600 MANDRA ATTICA, GREECE TEL.:+30 210 5538700, FAX:+30 210 5550464  
THESSALONIKI: ETHN. ANTISTASEOS 114, 55134 KALAMARIA, TEL.:+30 2310 450000, FAX:+30 2310 493984

2/2

**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**